



GLOCK 45 Gen6



FRONT SIGHT
polymer



SLIDE STOP LEVER
ambidextrous

TRIGGER CONFIGURATION
triggerspring01 / connector 5 /
firing pin spring 24N (silver)



REAR SIGHT
polymer



MAGAZINE
17 rds



MAGAZINE CATCH
reversible



PERFECTION

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

www.glock.com



DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	189	7,44
2. SLIDE LENGTH (cpl.)	174	6,85
3. WIDTH (OVERALL)	34,4	1,35
4. SLIDE WIDTH	25,5	1,00
5. HEIGHT INCL. MAGAZINE	139	5,47
6. SIGHT RADIUS (POLYMER)	157	6,18
SIGHT RADIUS (STEEL)	156	6,14
SIGHT RADIUS (GNS)	155	6,10
7. TRIGGER DISTANCE	68	2,68
8. BARREL DISTANCE	20	0,79

VARIABLE DIMENSIONS

		mm	in.
MEDIUM BACKSTRAP w/o beaver tail (+ 2 mm 0.08 in.)	1. LENGTH (OVERALL)	191	7,52
	7. TRIGGER DISTANCE	70	2,76
LARGE BACKSTRAP w/o beaver tail (+ 4 mm 0.16 in.)	1. LENGTH (OVERALL)	193	7,60
	7. TRIGGER DISTANCE	72	2,83

TECHNICAL DATA



CALIBER

9x19



MAG. CAPACITY

17 rds



BARREL PROFILE

hexagonal (GMB)



BARREL LENGTH

mm	in.
102	4,02



LENGTH OF TWIST

mm	in.
250	9,84



WEIGHT

without magazine	
g	oz
575	20,28



WEIGHT

with empty magazine	
g	oz
655	23,10



WEIGHT*

with loaded magazine	
g	oz
865	30,51



TRIGGER TRAVEL

mm	in.
12,5	0,49

TRIGGER PULL

N	lbf
26	5,8

* depending on the ammunition used